

StraPack RQ-8A

FULLY AUTOMATED STRAPPING MACHINE



Easy strap loading, no need to remove from conveyor line



Ready to operate in less than 25 seconds



Robust, portable design with locking castors



Compatible with Conveyor Speeds of up to 30m/ min

The StraPack RQ-8A is a fully automatic strapping machine suitable for integration into production line systems.

FEATURES & BENEFITS

Self-Correcting Technology

If the RQ-8 is operated without a package on the table, the strap forms a small loop which is ejected from the sealing unit. The machine then re-feeds ready for the next cycle.

Self-Diagnostic Function

Programmable microprocessor constantly monitors critical functions. Any irregularity is immediately displayed.

Variable Tension

A wide range of tension can be selected via a single dial. Tension capability up to 80kg.

Reliable Motor & Drive Mechanism

Self-lubricating design and minimal moving parts reduces wear & tear and increases operational life.

Energy Saving Auto Shut-Off

Machine enters standby mode after 3 minutes - thereby saving energy.

Dimensions	Width	1252 mm
	Depth	611 mm
	Height	1403 mm
	Weight	230 kg
Arch Size	W 650 mm x H 500 mm	
Conveyor Height	798 mm	
Minimum Package Size	W 170 x H 80 x L 180 mm	
Maximum Package Size	W 550 x H 430 mm	
Joint / Strap / Coil	Heat Seal/ Polypropylene/ ID 200 x OD 450 x W 200 mm	
Strap Width	9, 12 mm	
Strap Tension	Up to 40 kg, Stroke 300 mm	
Power Supply	230/240 volts standard (110 volt optional)	

Conveyor Speed Information

Inverter Cycle	Conveyor Speed (per min)
20 Hz	9.8 m
30 Hz	14.7 m
40 Hz	19.6 m
50 Hz	24.5 m
60 Hz (Max)	29.4 m

Max Package Weight	Max Conveyor Speed (per min)
20 kg	30 m
25 kg	24 m
30 kg	20 m
35 kg	17 m
40 kg	15 m



Gordian House, Brunel Road, Houndmills Industrial Estate, Basingstoke, Hampshire RG21 6XX, UK.



www.gordianstrapping.co.uk



01256 394444



sales@gordianstrapping.com